

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/063037 A1

- (51) International Patent Classification⁷: B65D 33/00 (74) Agent: KLOOSTER, J., H.; Muller & Eilbracht B.V.,
P.O. Box 1080, NL-2260 BB Leidschendam (NL).
- (21) International Application Number: PCT/NL2003/000957 (81) Designated States (*national*): AU, CA, CN, JP, KP, KR,
MW, NO, NZ, PL, RU, US, ZA.
- (22) International Filing Date: 31 December 2003 (31.12.2003) (84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (25) Filing Language: Dutch
- (26) Publication Language: English
- (30) Priority Data: 1022290 31 December 2002 (31.12.2002) NL
- (71) Applicant and
(72) Inventor: NIEUWENHUIS, Gerrit, Jan [NL/NL]; 31,
Kalandersstraat, NL-7461 JL Rijssen (NL).
- Published:
— with international search report
— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FOIL BAG PROVIDED WITH A PUNCHED OPENING AND INCISIONS



(57) Abstract: The invention relates to an improvement of a foil bag which comprises flattened and optionally side folded foil bag portions, provided with a sealed bottom. Such foil bags, usually manufactured from polyethylene(PE) foil, are used in a packaging-machine, which is operated to open and subsequently position the bag into a box, crate or container. The foil bag is provided adjacent to its upper edge with one or more openings (6) having a diameter which is substantially equal or even greater than the external pin diameter of the support and whereas the foil bag is also provided with at least one foil bag portion provided with one or more incisions (10, 11) in the foil bag material at a certain distance from the opening in a circumferential direction, in such a way that during the opening process of the folded foil bag during a first step the front of the flat folded foil bag portion is pulled off the pin support and consequently during a second step the rearward flat foil bag portion is pulled off from the pin support in such a way that the incisions will remove the undesirable mutually adherence of the foil bag portions by introducing additional air between the opposite adhering foil bag portions while being pulled off the pin support so that the foil bag is completely and easily and problemless opened starting from the front flat foil bag portion whereafter the rearward flat foil bag portion is pulled off further from the pin support.